




HMSA BEARING MANUFACTURING LIMITED



skf FSAF 22517 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22517 T

FSAF 22517 T Bearing 2D drawings and 3D CAD models

d_a	74.612 mm
D_a	150 mm
C_a	45.796 mm
A_1	88.9 mm
A_2	198.438 mm
S	4.763 mm
b_a	35.719 mm
H	182.166 mm
H_1	95.25 mm
H_2	31.75 mm
J min.	250.825 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.975 mm
R_2	22.225 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	34.925 mm
Housing	FSAF 517
Stabilizing ring	SR-17-14
Taconite seal	TER 53
End plug (suffix Y)	EPR 9
Max. speed for Taconite seal	1050 r/min



HMSA BEARING MANUFACTURING LIMITED

P_{60°	61.4 kN
P_{90°	36.9 kN
P_{120°	23.1 kN
P_{150°	20.9 kN
P_{180°	25.4 kN
P_a	9.25 kN
Mass pillow block	17.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	110.56 g